



Tools: Torque

Transmission Line Systems

- Factory-certified calibration to ensure a secure connection between connector and device
- Available for all popular interfaces

JMA part number	Image	Hex width	Torque specifications	Shipping dimensions	Shipping weight	Compatible interfaces
TQ-716-F2.2		0.438 in. 11 mm	2.2 +0.4/-0.0 lbf·ft 2.98 +0.54/-0.00 N·m	9.0 x 1.0 x 2.0 in. 22.86 x 2.54 x 5.08 cm	0.49 lb 0.22 kg	Nex10
TQ-916-F2.2		0.630 in. 16 mm	2.2 +0.4/-0.0 lbf·ft 2.98 +0.54/-0.00 N·m	9.0 x 1.0 x 2.0 in. 22.86 x 2.54 x 5.08 cm	0.49 lb 0.22 kg	2.2-5
TW1412		0.750 in. 19 mm	14.0 +1.4/-0.0 lbf·in 1.58 +0.16/-0.00 N·m	10.0 x 1.0 x 2.0 in. 25.4 x 2.54 x 5.08 cm	0.55 lb 0.25 kg	N-type
TQ-78-F8		0.875 in. 22 mm	8.0 +0.8/-0.0 lbf·ft 10.85 +1.08/-0.00 N·m	10.0 x 1.0 x 2.0 in. 25.4 x 2.54 x 5.08 cm	0.58 lb 0.26 kg	4.1-9.5 (Mini-DIN) 4.3-10
TQ-114-F18		1.250 in. 32 mm	18.0 +1.8/-0.0 lbf·ft 24.4 +2.44/-0.00 N·m	13.0 x 1.50 x 4.0 in. 33.02 x 3.81 x 10.16 cm	1.72 lb 0.78 kg	7-16 DIN

QUESTIONS? VISIT WWW.TALLEYCOM.COM OR CONTACT TALLEY AT 800.949. 7079 OR SALES@TALLEYCOM.COM TODAY.