



Cold shrink Kit for 7/8 in to 1/4 in through 1/2 in connections

## Product Classification

**Product Type** Cold shrink kit

## Dimensions

**Nominal Size** 1/2 in | 1/4 in | 7/8 in  
**Cable Diameter for Seal, maximum** 21.34 mm | 0.84 in  
**Cable Diameter for Seal, minimum** 7.37 mm | 0.29 in  
**Inner Diameter** 51.31 mm | 2.02 in  
**Length** 254.00 mm | 10.00 in  
**Width** 53.85 mm | 2.12 in

## General Specifications

**Application** Provides additional moisture seal for cable connections  
**Applications per Kit** One 1/4 in–1/2 in to 7/8 in  
**Color** Black  
**Includes** One EPDM rubber tube | One sealing foam strip  
**Material Type** EPDM rubber  
**Ordering Note** CommScope® non-standard product  
**Package Quantity** 1

## Mechanical Specifications

**UV Resistance Test Method** UV condensation reference ASTM-G-53, light source UVA 340 fluorescent lamp  
**UV Resistance, minimum with no degradation** =1000 hours  
**Weather Resistance Test Method** 04AS00-03.6.0 | MIL-STD-1344A, Method 1002

## Packed Dimensions

**Height** 30.0 cm | 11.8 in  
**Length** 4.6 cm | 1.8 in  
**Shipping Weight** 0.18 kg | 0.40 lb  
**Width** 7.0 cm | 2.8 in

## Regulatory Compliance/Certifications

**Agency**

RoHS 2011/65/EU  
China RoHS SJ/T 11364-2006  
ISO 9001:2008

**Classification**

Compliant  
Below Maximum Concentration Value (MCV)  
Designed, manufactured and/or distributed under this quality management system

