



UA-3

Angle Adapter, universal, snap-in, 3/4 in through hole

Dimensions

| | | | |
|----------------|----------|--|---------|
| Inside Length | 25.40 mm | | 1.00 in |
| Inside Width | 22.23 mm | | 0.88 in |
| Outside Length | 50.80 mm | | 2.00 in |
| Outside Width | 57.15 mm | | 2.25 in |

General Specifications

| | |
|------------------|---|
| Adapter Type | Angle adapter |
| Material Type | Stainless steel |
| Ordering Note | CommScope® standard product in Asia Pacific CommScope® standard product in the United States and Canada |
| Package Quantity | 10 |

Mechanical Specifications

| | |
|------------------------------|------------------------------|
| Installation Torque, maximum | 15.0 ft lb |
| Installation Torque, minimum | 11.0 ft lb |
| Material Thickness | 2.667 mm 0.105 in |
| Maximum Loading | Triple stack, 1-5/8 in cable |
| Mounting | 3/4 in through hole |

Packed Dimensions

| | | | |
|-----------------|---------|--|---------|
| Height | 25.0 cm | | 9.8 in |
| Length | 12.0 cm | | 4.7 in |
| Shipping Weight | 2.32 kg | | 5.11 lb |
| Width | 14.0 cm | | 5.5 in |

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| ISO 9001:2008 | Designed, manufactured and/or distributed under this quality management system |