



LPX Series

Next Generation Low Profile Power Supplies

LPX-10, LPX-14, LPX-18, LPX-25



The LPX Series is the next generation of DuraComm's popular and reliable LP desktop power supply. We enhanced the electronic filtering and noise shielding, added auto ranging AC input, and adjustable DC output, all while maintaining the rugged 7 inch standard design. The improved efficiency meets DoE level VI green energy standards.



| | LPX-10 | LPX-14 | LPX-18 | LPX-25 |
|---|---|--------|-----------------------|--------|
| Input Voltage (Nominal) | 90-264 VAC or 127-370 VDC | | | |
| Output voltage | 13.8V | | | |
| OUTPUT RIPPLE & NOISE (ON FULL LOAD, PEAK TO PEAK) | 150 mV | | | |
| OUTPUT CURRENT, CONTINUOUS | 8.7A | 13A | 17.4A | 26A |
| CURRENT LIMIT | 10.9A | 16.3A | 21.7A | 32.6A |
| COOLING | Convection Cooled | | | |
| PROTECTIONS | Overload, over voltage, and over temperature | | | |
| ENVIRONMENTAL TEMPERATURE RANGE | -30 to +70 °C | | -22 to +158 ° F | |
| AC INPUT | Detachable power cord C/W NEMA 5-15P plug | | | |
| DC OUTPUT | Terminals w/ recessed hole DIA. 0.16" (4 mm) with set screw | | | |
| DIMENSIONS, (L x W x H) Shipping | 280 x 230 x 60 mm | | 11.02 x 9.06 x 2.36in | |
| DIMENSIONS, (L x W x H) Product | 192 x 178 x 45 mm | | 7.56 x 7.00 x 1.77 in | |
| WEIGHT | 1 KG | | 2.21 LB | |

*NOTE: Specifications are subject to change without notice

Edited: May 11, 2018