

INTERMODULATION CONTROL DEVICES

300 - 650 MHz

Model No. List Price	Description	Frequency	Pwr: Input Refl	Bandwidth: Fixed	Insertion Loss	Isolation	Load Termination	Actual Dimensions Inches Metric	Ship Wt. lbs kg.
W8550/34	Dual Isolator, 30/60 Watt Load	300-650	125 W 60 W		0.45 dB	60+ dB	30/60 W	1 3/8 x 5 1/2 x 5 5/8 35 x 140 x 143	3 1.4
W8550/34A	Dual Isolator, 30/75 Watt Load	300-650	125 W 75 W		0.45 dB	60+ dB	30/75 W	1 3/8 x 5 1/2 x 6 3/4 35 x 140 x 172	4 1.9
W8550/34B	Dual Isolator, 30/75 Watt Load	300-650	125 W 75 W		0.45 dB	60+ dB	30/75 W	1 3/8 x 5 1/2 x 6 3/4 35 x 140 x 172	4 1.9
W8550/35	Dual Isolator, 30/125 Watt Load	300-650	125 W 125 W		0.45 dB	60+ dB	30/125 W	3 x 11 1/2 x 9 3/8 77 x 293 x 239	7 3.2



W8550/34



W8550/34A



W8550/35

ISOLATORS & CIRCULATORS