



LDF4-50A SureFlex® Jumper with interface types 7-16 DIN Male and 7-16 DIN Male Right Angle, 4.572 m

Product Classification

Product Series LDF4-50A
Product Type SureFlex® Premium, static PIM

General Specifications

Body Style, Connector A Straight
Body Style, Connector B Right angle
Interface, Connector A 7-16 DIN Male
Interface, Connector B 7-16 DIN Male
Length 4.572 m | 15.000 ft
Nominal Size 1/2 in
Specification Sheet Revision Level B

Electrical Specifications

3rd Order IMD Static -159.00 dBc | -116.00 dBm
3rd Order IMD Static Test Method Two +43 dBm carriers
DTF, Connector A -34.00 dB
DTF, Connector B -30.00 dB

Jumper Assembly Sample Label

Batch 0123456789 **Manufacturing Date** (two digit year and week) 1240
Manufacturing Plant US22 **Product Revision** /A

Part Number F4-DMDM-2M-D

Serial Number 12US220001242

COMMSCOPE® Andrew Solutions™
F4-DMDM-2M-D
 2 M (6.562 FT)
 SUREFLEX ASSEMBLY
 U.S. PATENT 5802710
 Product of UNITED STATES

Return Loss/VSWR

Frequency Band	VSWR	Return Loss (dB)
698–960 MHz	1.08	28.00
1700–2200 MHz	1.08	28.00
2200–2700 MHz	1.13	24.00

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

Included Products

LDF4-50A — LDF4-50A, HELIAX® Low Density Foam Coaxial Cable, corrugated copper, 1/2 in, black PE jacket