



## MC-DPM35M-6-126

**Monopole Co-location Dual Pipe Mount Kit, 12 in to 50 in OD, 4 ft 9 in face, includes pipes**

### Dimensions

Face Width	1.4 m   4.8 ft
Mounting Diameter, maximum	1270.0 mm   50 in
Mounting Diameter, minimum	304.8 mm   12 in
Pipe Outer Diameter	88.9 mm   3 1/2 in
Height	3200.4 mm   126.0 in
Length	355.6 mm   14.0 in
Mounting Circumference, maximum	3990.3 mm   157.1 in
Mounting Circumference, minimum	1196.3 mm   47.1 in
Weight	469.5 kg   1035.1 lb
Width	1447.8 mm   57.0 in

### Environmental Specifications

Man Rating	250 lb vertical man load at 15 mph (BWS)
Wind Rating	120 mph (BWS) at 150 ft AGL   140 mph (3-second gust) at 150 ft AGL using Exposure D per FBC
Wind Rating Criteria	Two 72 in x 8 in panel antennas per sector
Wind Rating Test Method	TIA/EIA-222-G

### General Specifications

Product Type	Co-location dual pipe mount kit
Pipe Length	3200.4 mm   126.0 in
Pipe, quantity	6
Includes	Dual pipe frames   Pipe mounts   Ring mount
Material Type	Hot dip galvanized steel
Mounting	Monopole, 304.8–1270 mm (12–50 in) OD
Package Quantity	1
Sectors, quantity	3
Stand-off Distance	355.6 mm   14.0 in

### Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

#### \* Footnotes

# Product Specifications

COMMSCOPE®

MC-DPM35M6-126

POWERED BY



---

Man Rating	BWS—Base Wind Speed
Wind Rating	BWS—Base Wind Speed; FBC—Florida Building Code