MTC4112 | CORE RRU MOUNT



Core RRU Mount with 12" Stand-off - Mounts to Spine on G2 Series Mounts

Designed for G2 RHDX Series Mounts with or without Extended Spine• Internal tower RRU mount• Decreased PIM from radio relocation• Increased mount stability• Decreased face loading• Increased mount versatility without the need for a new RRUmountNOTE: Requires use of RR-FA2 RRU brackets

Product Classification

Product Type	Remote radio head unit mount

General Specifications

Mounting	Pipe, 88.9 mm (3-1/2 in) OD

Dimensions

Height	3,048 mm | 120 in
Length	419.1 mm | 16.5 in
Compatible Diameter	88.9 mm | 3.5 in
Mounting Diameter, maximum	88.9 mm | 3.5 in
Mounting Diameter, minimum	88.9 mm | 3.5 in
Stand-off Distance	304.8 mm | 12 in

Material Specifications

Material Type	Hot dip galvanized steel

Mechanical Specifications

Wind Rating	For Specifications, please contact steelproducts@commscope.com or call 800-255-1479

Packaging and Weights

Included	Clamps | Hardware | Stand-off
Packaging quantity	1
Weight, net	50.476 kg | 111.28 lb

Regulatory Compliance/Certifications

©2023 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: March 23, 2023

MTC4112 | CORE RRU MOUNT

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

* Footnotes

Wind Rating	BWS—Base Wind Speed; FBC—Florida Building Code

800.949.7079 sales@talleycom.com Order online today at www.talleycom.com

©2023 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope. All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: March 23, 2023