Product Specifications

POWERED BY ANDREW





PML-SU2-B

Large Leg Universal Sliding Pipe Mount Kit for 2-3/8 in OD pipe

Dimensions

Mounting Diameter, maximum	406.4 mm | 16 in
Mounting Diameter, minimum	0.0 mm | 0 in
Pipe Outer Diameter	60.3 mm | 2 3/8 in
Height	127.0 mm | 5.0 in
Length	304.8 mm | 12.0 in
Weight	32.3 kg | 71.2 lb
Width	304.8 mm | 12.0 in

Environmental Specifications

Wind Rating	120 mph (BWS) at 150 ft AGL
Wind Rating Test Method	TIA/EIA-222

General Specifications

Product Type	Pipe mount
Pipe, quantity	0
Stand-off Distance	203.2 mm | 8.0 in
Tower Taper	Non-tapered | Tapered
Includes	Sliding pipe mount brackets | Universal saddle mount
Material Type	Hot dip galvanized steel
Mounting	Angle 60°, 406.4 mm (16 in) | Angle 90°, 304.8 mm (12 in) | Straight or tapered legs up to 406.4 mm (16 in) OD
Note	One 96 in x 8 in panel antenna per sector
Package Quantity	1

Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system

* Footnotes

Wind Rating	BWS—Base Wind Speed; FBC—Florida Building Code

©2015 CommScope, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of CommScope.
All specifications are subject to change without notice. See www.commscope.com for the most current information. Revised: August 7, 2013